

Material and Application Guide

1³/₄ Roofing Gravel – Highland



EDW. C. LEVY CO.

8800 Dix Avenue, Detroit, Michigan 48209

Phone (313) 429-LEVY

Fax (313) 429-2448

e-mail sales@edwclevy.net

<http://www.edwclevy.com>

Material: Natural Gravel

Product: 1³/₄ Roofing Gravel – Commercial

Location: American Aggregate, Highland Plant

Applications Ballast aggregate for rubber roofing systems
Decorate stone for landscaping

Description: An open graded coarse aggregate, produced by washing and screening natural gravel. The particles are sized from 1³/₄" (44.0mm) to 1" (25.0mm) and were formed by the natural disintegration of numerous types and colors of rocks by glacial or riverbed action into primarily round particles.



1³/₄ Roofing Natural Gravel – Actual size shown

Material Properties: Commercial

1³/₄ Roofing Natural Gravel is produced to commercial requirements.

Gradation:

U.S. Sieve	2"	1½"	1"	¾"	½"
Metric Sieve	50.0mm	37.5mm	25.0mm	19.0mm	12.5mm
2008 Average	100	76	3	0	0

General Usage Guide:

The 1³/₄ Roofing Natural Gravel should be evenly spread over the prepared rubber membrane at the rate shown below.

Field Estimating Quantities:

Typical 1 ³ / ₄ Roofing Natural Gravel requirements per square (100 sq. ft.) of roof surface	1,500 lbs
--	-----------

This information is not to be taken as warranty or representation for which we assume legal responsibility nor as permission or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation and verification.